

**PS25/200 FT5,5**

 \*Image is for illustrative purposes only 

## Professional two-stage belt driven compressor, ideal for heavy and continuous use.

A two-stage three-phase belt driven compressor designed for intensive use by professionals, it is equipped with a 5.5 hp pumping unit with highly efficient operation cast iron cylinders with large manifolds for better cooling and robust metal belt covers protecting moving parts. The 200-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.

### TECHNICAL DATA

|                                 |        |               |
|---------------------------------|--------|---------------|
| Product code                    |        | SGLN701PWS110 |
| Lubrication                     |        | Lubricated    |
| Compressor pump                 |        | PS25          |
| Air receiver (l)                |        | 200           |
| Power                           | Hp     | 5,5           |
|                                 | kW     | 4             |
| Max. pressure                   | bar    | 11            |
|                                 | p.s.i. | 160           |
| Nr. of cylinders                |        | 2             |
| Air displacement                | l/min. | 612           |
|                                 | c.f.m. | 21,6          |
| R.P.M.                          |        | 1184          |
| Voltage / Frequency (Volt / Hz) |        | 400/50        |
| Type motor                      |        | Electric      |
| Gross weight                    | kg     | 128           |
|                                 | lb     | 282,2         |
| Packaging dimensions LxWxH (mm) |        | 1435x470x1240 |
| EAN code                        |        | 8016738792959 |