

PS25/500 FT5,5
**Image is for illustrative purposes only*

Professional two-stage belt driven compressor, ideal for heavy and continuous use.

A two-stage three-phase belt driven compressor designed for intensive use by professionals, it is equipped with a 5.5 hp pumping unit with highly efficient operation cast iron cylinders with large manifolds for better cooling and robust metal belt covers protecting moving parts. The 500-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.



TECHNICAL DATA

| | | |
|---------------------------------|---------------|-------|
| Product code | SGTN701PWS113 | |
| Lubrication | Lubricated | |
| Compressor pump | PS25 | |
| Air receiver (l) | 500 | |
| Power | Hp | 5,5 |
| | kW | 4 |
| Max. pressure | bar | 11 |
| | p.s.i. | 160 |
| Nr. of cylinders | 2 | |
| Air displacement | l/min. | 612 |
| | c.f.m. | 21,6 |
| R.P.M. | 1184 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Type motor | Electric | |
| Gross weight | kg | 218 |
| | lb | 480,6 |
| Packaging dimensions LxWxH (mm) | 2010x650x1330 | |
| EAN code | 8016738792980 | |