

PS30/270 FT5,5 SD



# Professional two-stage belt driven compressor, ideal for heavy and continuous use.

A two-stage three-phase belt driven compressor with star-delta starter designed for intensive use by professionals, it is equipped with a 5.5 hp pumping unit with highly efficient operation cast iron cylinders with large manifolds for better cooling and robust metal belt covers protecting moving parts. The 270-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.

## TECHNICAL DATA

|                                 |               |       |
|---------------------------------|---------------|-------|
| Product code                    | SLNN705PWS121 |       |
| Lubrication                     | Lubricated    |       |
| Compressor pump                 | PS30          |       |
| Air receiver (l)                | 270           |       |
| Power                           | Hp            | 5,5   |
|                                 | kW            | 4     |
| Max. pressure                   | bar           | 11    |
|                                 | p.s.i.        | 160   |
| Nr. of cylinders                | 2             |       |
| Air displacement                | l/min.        | 729   |
|                                 | c.f.m.        | 25,6  |
| R.P.M.                          | 1000          |       |
| Voltage / Frequency (Volt / Hz) | 400/50        |       |
| Type motor                      | Electric      |       |
| Gross weight                    | kg            | 170   |
|                                 | lb            | 374,8 |
| Packaging dimensions LxWxH (mm) | 1640x560x1330 |       |
| EAN code                        | 8016738793062 |       |