

PS50/500 AP FT10

Two-stage belt driven high-pressure compressor, suitable for car repair shops and tyre shops.

A two-stage high pressure belt driven compressor designed for intensive use by professionals, it is equipped with a 10 hp pumping unit with highly efficient operation cast iron cylinders with large manifolds for better cooling and robust metal belt covers protecting moving parts. The 500-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.



TECHNICAL DATA

| | | |
|---------------------------------|---------------|-------|
| Product code | SMTN901PWS131 | |
| Lubrication | Lubricated | |
| Compressor pump | PS50 | |
| Air receiver (l) | 500 | |
| Power | Hp | 10 |
| | kW | 7,5 |
| Max. pressure | bar | 14 |
| | p.s.i. | 203 |
| Nr. of cylinders | 2 | |
| Air displacement | l/min. | 857 |
| | c.f.m. | 30,2 |
| R.P.M. | 800 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Type motor | Electric | |
| Gross weight | kg | 323 |
| | lb | 712,1 |
| Packaging dimensions LxWxH (mm) | 2270x860x1660 | |
| EAN code | 8016738793161 | |