

PS50/500TD FT10+10 SD

*Image is for illustrative purposes only

Two-stage belt driven tandem compressor that guarantees very high performance.

Two-stage three-phase Tandem belt driven compressor with star delta starter suitable for high performance by professionals due to higher air intake and higher volumetric efficiency. It is equipped with two highly efficient 10 hp pumping units with cast iron cylinders with large manifolds and finned tubes for better air cooling and robust metal belt covers protecting moving parts. The 500-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.



TECHNICAL DATA

| | | |
|---------------------------------|---------------|---------|
| Product code | SMUN905PWS149 | |
| Lubrication | Lubricated | |
| Compressor pump | PS50 | |
| Air receiver (l) | 500 | |
| Power | Hp | 10+10 |
| | kW | 7,5+7,5 |
| Max. pressure | bar | 11 |
| | p.s.i. | 160 |
| Nr. of cylinders | 2 | |
| Air displacement | l/min. | 2148 |
| | c.f.m. | 75,7 |
| R.P.M. | 1000 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Type motor | Electric | |
| Gross weight | kg | 459 |
| | lb | 1012 |
| Packaging dimensions LxWxH (mm) | 2270x860x1660 | |
| EAN code | 8016738793345 | |