

SILBOX 3 PS30/500 FT7,5 +ESS

Professional silenced two-stage belt driven compressor, complete with tank and dryer.

Professional silenced compressor with dryer, with the lowest noise level in its class, designed to solve the problem of noise in work environments. The powerful 7.5 hp pumping unit guarantees the highest level of efficiency and reliability. It is also equipped with an additional intake silencer, a belt tensioning slide that adjusts belt tension and facilitates replacement, and a forced fan for better cooling. The control panel is positioned for easy reading and operation. The opening front door allows easy maintenance. Easily transportable thanks to the bar placed between the feet at the base of the 500-litre tank.



TECHNICAL DATA

Lubrication Lubricated Compressor pump PS30 Air receiver (I) 500 Power Hp 7,5 kW 5,5 bar 11 p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement I/min. 872 R.P.M. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight Bg 387 Ib 853,2 Packaging dimensions LxWXH (mm) 2005x970x1660 EAN code 8016738793536	Product code		SLTT801PWS301
Air receiver (I) 500 Power Hp 7,5 kW 5,5 bar 11 p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement I/min. 872 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 B 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Lubrication		Lubricated
Power Hp 7,5 kW 5,5 bar 11 p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement I/min. 872 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Compressor pump		PS30
Power kW 5,5 Max. pressure bar 11 p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement I/min. 872 c.f.m. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Air receiver (I)		500
kW 5,5 bar 11 p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement I/min. 872 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric kg 387 Cross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Power	Нр	7,5
Max. pressure p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement 1/min. 872 c.f.m. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660		kW	5,5
p.s.i. 160 Sound level (dB(A)) 69 Nr. of cylinders 2 Air displacement I/min. 872 c.f.m. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Max. pressure	bar	11
Nr. of cylinders 2 Air displacement I/min. 872 c.f.m. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660		p.s.i.	160
Air displacement I/min. 872 c.f.m. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor kg 387 Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Sound level (dB(A))		69
Air displacement c.f.m. 30,7 R.P.M. 1200 Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Nr. of cylinders		2
R.P.M. 30,7 Voltage / Frequency (Volt / Hz) 1200 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Air displacement	l/min.	872
Voltage / Frequency (Volt / Hz) 400/50 Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660		c.f.m.	30,7
Type motor Electric Gross weight kg 387 Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	R.P.M.		1200
kg 387 lb 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Voltage / Frequency (Volt / Hz)		400/50
Gross weight Ib 853,2 Packaging dimensions LxWxH (mm) 2005x970x1660	Type motor		Electric
Packaging dimensions LxWxH (mm) 853,2 2005x970x1660	Gross weight	kg	387
		lb	853,2
EAN code 8016738793536	Packaging dimensions LxWxH (mm)		2005x970x1660
	EAN code		8016738793536

^{*}Sound pressure level measurement carried out at a distance of 7 metres.