

DARWIN 16-13
Screw compressor with belt transmission.

Three-phase belt-transmission lubricated screw compressor with DNAir1 electronic controller and star/delta starterer. Soundproof cab in hot-dip galvanised sheet metal for maximum silence


TECHNICAL DATA

| | | |
|---------------------------------|---------------|------|
| Product code | V60NW92PWSA87 | |
| Lubrication | Lubricated | |
| Air-end | FS50 | |
| Air receiver (l) | - | |
| Power | 15 | |
| Air outflow | l/min. | 1750 |
| | m3/min. | 1,75 |
| | c.f.m. | 62 |
| Max. pressure | bar | 13 |
| | p.s.i. | 189 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 68 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 3/4" | |
| Controller | DNAir1 | |
| Type motor | Electric | |
| Energy efficiency | IE3 | |
| Gross weight (kg) | 248 | |
| Net weight (kg) | 234 | |
| Packaging dimensions LxWxH (mm) | 940x770x1150 | |
| Net Dimensions LxWxH (mm) | 820x680x980 | |

*Sound pressure level measurement carried out at a distance of 7 metres.