

DARWIN 38-08 DV

Belt transmission screw compressor, with high energy efficiency.

Lubricated screw compressor with belt transmission, DNAir2 electronic controller and inverter regulation. Soundproof cab in painted sheet metal and radial ventilation for maximum quiet operation


TECHNICAL DATA

| | | |
|---------------------------------|----------------------|-------------|
| Product code | V60BK97PWSA87 | |
| Lubrication | Lubricated | |
| Air-end | FS140 | |
| Air receiver (l) | - | |
| Power | 37 | |
| Air outflow | l/min. | 2400 / 6000 |
| | m ³ /min. | 2.4 / 6 |
| | c.f.m. | 85 / 212 |
| Max. pressure | bar | 8 |
| | p.s.i. | 116 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 68 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 1 - 1/4" | |
| Controller | DNAir2 | |
| Type motor | Electric | |
| Energy efficiency | IE3 | |
| Gross weight (kg) | 817 | |
| Net weight (kg) | 748 | |
| Packaging dimensions LxWxH (mm) | 1690x1030x1730 | |
| Net Dimensions LxWxH (mm) | 1530x880x1440 | |

*Sound pressure level measurement carried out at a distance of 7 metres.