

## DARWIN 38-10 DV-D

## Belt transmission screw compressor, with high energy efficiency.

Lubricated screw compressor with belt transmission, DNAir2 electronic controller and inverter regulation. Soundproof cab made of painted sheet metal and radial ventilation and complete with integrated dryer



## **TECHNICAL DATA**

Product code		V60BJ97PWSB87
Lubrication		Lubricated
Air-end		FS140
Air receiver (I)		-
Power		37
Air outflow	l/min.	2100 / 5300
	m3/min.	2.1 / 5.3
	c.f.m.	74 / 187
Max. pressure	bar	10
	p.s.i.	145
Nr. of stages		1
Sound level (dB(A))		68
Voltage / Frequency (Volt / Hz)		400/50
Connection (G)		1 - 1/2"
Controller		DNAir2
Type motor		Electric
Energy efficiency		IE3
Gross weight (kg)		898
Net weight (kg)		813
Packaging dimensions LxWxH (mm)		2050x1140x1670
Net Dimensions LxWxH (mm)		1860x910x1440

\*Sound pressure level measurement carried out at a distance of 7 metres.

FNA S.p.A. - Via Einaudi, 6 - 10070 Robassomero (TO) - Italy - www.finicompressors.com - info@fnacompressors.com