

**DARWIN 4.0-08-200 D**

## Screw compressor with belt transmission, complete with tank and dryer.

Three-phase belt-transmission lubricated screw compressor with DNAir1 electronic controller and star/delta starterer. Sheet metal soundproof cab complete with 200-litre tank and refrigerated dryer



### TECHNICAL DATA

|                                 |               |      |
|---------------------------------|---------------|------|
| Product code                    | V77JR92PWSB80 |      |
| Lubrication                     | Lubricated    |      |
| Air-end                         | FS14          |      |
| Air receiver (l)                | 200           |      |
| Power                           | 4             |      |
| Air outflow                     | l/min.        | 580  |
|                                 | m3/min.       | 0,58 |
|                                 | c.f.m.        | 20   |
| Max. pressure                   | bar           | 8    |
|                                 | p.s.i.        | 116  |
| Nr. of stages                   | 1             |      |
| Sound level (dB(A))             | 60            |      |
| Voltage / Frequency (Volt / Hz) | 400/50        |      |
| Connection (G)                  | 1/2"          |      |
| Controller                      | DNAir1        |      |
| Type motor                      | Electric      |      |
| Energy efficiency               | IE3           |      |
| Gross weight (kg)               | 232           |      |
| Net weight (kg)                 | 208           |      |
| Packaging dimensions LxWxH (mm) | 1540x620x1470 |      |
| Net Dimensions LxWxH (mm)       | 1430x550x1310 |      |

\*Sound pressure level measurement carried out at a distance of 7 metres.