

JUNIOR 7.5-10-270

Compact, direct drive transmission screw compressor, complete with tank.

Three-phase lubricated screw compressor with coaxial transmission for efficiency and reliability. Particularly compact and easy to install and maintain complete with 270 litre storage tank



TECHNICAL DATA

| | | |
|---------------------------------|---------------|------|
| Product code | V91P092PWS080 | |
| Lubrication | Lubricated | |
| Air-end | FS26 | |
| Air receiver (l) | 270 | |
| Power | 7,5 | |
| Air outflow | l/min. | 1050 |
| | m3/min. | 1,05 |
| | c.f.m. | 37 |
| Max. pressure | bar | 10 |
| | p.s.i. | 145 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 67 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 1/2" | |
| Controller | ETMII | |
| Type motor | Electric | |
| Gross weight (kg) | 222 | |
| Net weight (kg) | 194 | |
| Packaging dimensions LxWxH (mm) | 1320x850x1720 | |
| Net Dimensions LxWxH (mm) | 1200x600x1450 | |

*Sound pressure level measurement carried out at a distance of 7 metres.