

G-TEC 18.5-10-500

## Workstation complete with tank and dryer with line filters

Lubricated screw compressor with belt transmission, DNAir2 electronic controller. Cabin with radial ventilation and integrated refrigerated dryer complete with prefilter and microfilter. 500 litre tank



### TECHNICAL DATA

|                                 |         |      |               |
|---------------------------------|---------|------|---------------|
| Product code                    |         |      | V83SV92PWSB80 |
| Lubrication                     |         |      | Lubricated    |
| Air-end                         |         |      | FS50          |
| Air receiver (l)                |         |      | 500           |
| Power                           |         |      | 18,5          |
| Air outflow                     | l/min.  | 2500 |               |
|                                 | m3/min. | 2,5  |               |
|                                 | c.f.m.  | 88   |               |
| Max. pressure                   | bar     | 10   |               |
|                                 | p.s.i.  | 145  |               |
| Nr. of stages                   |         |      | 1             |
| Sound level (dB(A))             |         |      | 70            |
| Voltage / Frequency (Volt / Hz) |         |      | 400/50        |
| Connection (G)                  |         |      | 3/4"          |
| Controller                      |         |      | DNAir2        |
| Type motor                      |         |      | Electric      |
| Energy efficiency               |         |      | IE3           |
| Gross weight (kg)               |         |      | 610           |
| Net weight (kg)                 |         |      | 571           |
| Packaging dimensions LxWxH (mm) |         |      | 2070x800x1930 |
| Net Dimensions LxWxH (mm)       |         |      | 2000x760x1750 |

\*Sound pressure level measurement carried out at a distance of 7 metres.