

NOBEL 11-13-500 DV

Screw compressor with direct drive transmission, complete with tank.

Lubricated screw compressor with coaxial transmission and inverter control. LOGIN electronic controller. Compact and quiet, mounted on 500-litre tank



TECHNICAL DATA

| | | |
|---------------------------------|---------------|-------------|
| Product code | V83CF97PWSX80 | |
| Lubrication | Lubricated | |
| Air-end | FS50 | |
| Air receiver (l) | 500 | |
| Power | 11 | |
| Air outflow | l/min. | 373 / 1250 |
| | m3/min. | 0.37 / 1.25 |
| | c.f.m. | 13 / 44 |
| Max. pressure | bar | 13 |
| | p.s.i. | 189 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 67 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 3/4" | |
| Controller | LOGIN | |
| Type motor | Electric | |
| Energy efficiency | IE3 | |
| Gross weight (kg) | 436 | |
| Net weight (kg) | 395 | |
| Packaging dimensions LxWxH (mm) | 2070x800x1850 | |
| Net Dimensions LxWxH (mm) | 2000x750x1670 | |

*Sound pressure level measurement carried out at a distance of 7 metres.