

**NOBEL 90-13**

## Screw compressor with direct drive transmission.

Lubricated screw compressor with coaxial transmission. Modern and versatile LOGIN electronic controller. Compact and silent



### TECHNICAL DATA

|                                 |                |       |
|---------------------------------|----------------|-------|
| Product code                    | V60MS92PWSA87  |       |
| Lubrication                     | Lubricated     |       |
| Air-end                         | FS300          |       |
| Air receiver (l)                | -              |       |
| Power                           | 90             |       |
| Air outflow                     | l/min.         | 10400 |
|                                 | m3/min.        | 10,4  |
|                                 | c.f.m.         | 367   |
| Max. pressure                   | bar            | 13    |
|                                 | p.s.i.         | 189   |
| Nr. of stages                   | 1              |       |
| Sound level (dB(A))             | 67             |       |
| Voltage / Frequency (Volt / Hz) | 400/50         |       |
| Connection (G)                  | 2"             |       |
| Controller                      | LOGIN          |       |
| Type motor                      | Electric       |       |
| Energy efficiency               | IE4            |       |
| Gross weight (kg)               | 3125           |       |
| Net weight (kg)                 | 2927           |       |
| Packaging dimensions LxWxH (mm) | 2560x1660x2230 |       |
| Net Dimensions LxWxH (mm)       | 2330x1460x1980 |       |

\*Sound pressure level measurement carried out at a distance of 7 metres.