

PASCAL 7.5-10-500

Screw compressor with belt transmission.

Lubricated screw compressor with belt transmission, DNAir1 electronic controller and star/delta starterer complete with 500-litre tank. Soundproof cab for maximum quiet.



TECHNICAL DATA

|                                 |               |      |
|---------------------------------|---------------|------|
| Product code                    | V83TV92PWSA80 |      |
| Lubrication                     | Lubricated    |      |
| Air-end                         | FS26          |      |
| Air receiver (l)                | 500           |      |
| Power                           | 7,5           |      |
| Air outflow                     | l/min.        | 1000 |
|                                 | m3/min.       | 1    |
|                                 | c.f.m.        | 35   |
| Max. pressure                   | bar           | 10   |
|                                 | p.s.i.        | 145  |
| Nr. of stages                   | 1             |      |
| Sound level (dB(A))             | 66            |      |
| Voltage / Frequency (Volt / Hz) | 400/50        |      |
| Connection (G)                  | 1/2"          |      |
| Controller                      | DNAir1        |      |
| Type motor                      | Electric      |      |
| Energy efficiency               | IE3           |      |
| Gross weight (kg)               | 328           |      |
| Net weight (kg)                 | 304           |      |
| Packaging dimensions LxWxH (mm) | 2070x800x1680 |      |
| Net Dimensions LxWxH (mm)       | 2000x650x1500 |      |

\*Sound pressure level measurement carried out at a distance of 7 metres.